



Multi-zone remote desk microphone, with electronic switches, for amplifiers [Vivaldi Ulisse MZ6120BTK](#), [Vivaldi Ulisse MZ6240BTK](#), [Vivaldi Ulisse MZ6350BT](#), [Vivaldi Ulisse MZ6350BTK](#), [Vivaldi Ulisse MZ6500BT](#), [Vivaldi Ulisse MZ6500BTK](#)

The base provides 6 zones call at 300 m. maximum distance, via cable CAT6. Every amplifier supports up to 6 desk microphones, daisy chain connected. BM6 can be preset with different priority levels, by dip switches on rear panel of each of them.

Table top microphone is powered from the amplifier.

Features:

6 electronic switches to select the zone (ZONE1, ZONE2, ZONE3, ZONE4, ZONE5, ZONE6). - Gooseneck microphone connector.

- Power supply light indicator..
- Communication light indicator.
- Busy light (occupied).
- Speaker light marker 1-6.
- Speaker light selectors 1-6.
- Chime (three tones)/Talk push button (to maintain pressed during speech).
- ALL selector for call all zones (1-6 selector).
- Switch ON/OFF.

RJ45 port to connect the following bases via daisy chain.

RJ45 communication port with amplifier [Vivaldi Ulisse MZ6120BTK](#), [Vivaldi Ulisse MZ6240BTK](#), [Vivaldi Ulisse MZ6350BT](#), [Vivaldi Ulisse MZ6350BTK](#), [Vivaldi Ulisse MZ6500BT](#), [Vivaldi Ulisse MZ6500BTK](#).

VIVALDI

Gain microphone control.

Local Aux input (alternatively to microphone).

Priority dip switches.

Max. distance from amplifier to the connected base is 300 mt.

Goosneck from 41cm.

Power supply from amplifier by CAT6 cable RJ45 connector.

Daisy chain linkable (up to 6 BM6) for max. length of 300 mt.

Weight 0,9 Kg.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice



Images

Vivaldi Ulisse BM6



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272