



Multi-zone remote desk microphone, with electronic switches, for amplifiers [Vivaldi Ulisse MS6060BT](#), [Vivaldi Ulisse MS6120BT](#), [Vivaldi Ulisse MS6120BTK](#), [Vivaldi Ulisse MS6240BTK](#).

The base provides 6 zones call at 300 m. maximum distance, via cable CAT6. Every amplifier supports up to 6 desk microphones, to 6 Lan link connected or daisy chain connected. 6 desk microphones can be preset with different priority levels, by dip switches on rear panel of each of them.

Table top microphone is powered from the amplifier.

Features:

6 electronic switches to select the zone (ZONE1, ZONE2, ZONE3, ZONE4, ZONE5, ZONE6). - Gooseneck microphone connector.

- Input gooseneck microphone
- Power supply light indicator..
- Communication light indicator.
- Busy light (occupied).
- Zone light marker
- Zone selector Switch
- All zone selector switch
- ON/OFF switch
- RJ45 port for matrix connection or link to another base (via CAT6 cable)
- Gain microphone gain
- AUX input
- Dip switch for addressing

VIVALDI

-1-6Addresses set up diagram

-RJ45 port to connect the following bases via daisy chain

-RJ45 communication port with amplifier [Vivaldi Ulisse MS6060BT](#), [Vivaldi Ulisse MS6120BT](#), [Vivaldi Ulisse MS6120BTK](#), [Vivaldi Ulisse MS6240BTK](#).

Gain microphone control.

Local Aux input

Priority Dip switches

Max. distance from amplifier to the connected base is 300 mt.

Goosneck from 41cm.

Power supply from amplifier by CAT6 cable RJ45 connector.

Daisy chain linkable (up to 6 BM6) for max. length of 300 mt.

Weight 0,9 Kg.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice



Images

Vivaldi Ulisse BS6



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272