



Rectangular speaker, 2-way built-in, **HI-FI**.

Loudspeaker: woofer 13,5 cm Kevlar.

Dome tweeter 2,5 cm **eyeball (in case of installations in not optimal environments it allows to give directivity to high frequencies, while not decreasing quality of listening).**

Neodymium magnet. Silk diaphragm.

Power 50W RMS.

Musical power 100W.

Suggested amplification from 10 to 60 W RMS.

Impedance 8 Ω .

Frequency response 55-20000 Hz.

Sensitivity 89 dB.

Dispersion angle 120° (V/O)

Speaker dimensions (WxHxD) 190x280x60 mm.

In-built hole (WxH) 160x245 mm.

Weight 1,60 Kg.

Installation on plasterboard, wood walls or similar: no accessories needed, the speaker is provided in the rear with hook-shaped anchors for stable fixing.

Installation in-wall: by means of in-built case [Vivaldi Ulisse SR1](#).

Installation in-wall but room dividers or thick walls: by means of in-built case [Vivaldi Ulisse SR1S](#).

VIVALDI

Colour white RAL9016, paintable (please, view [Vivaldi Giove GIADA13L.R](#)).

Cabinet: ABS with metal protection grille.

Working temperature from -20° to +65°.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice



Images

Vivaldi Giove GIADA13L



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA

Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it

P.IVA e C.F. 02880360272