



Garden speaker, **Hi-Fi**, 2 way coax, IP56*waterproof.

Woofer: 16,5 cm polypropylene.

Tweeter: 3cm titanium neodymium magnet.

Nominal power 100V: 2/4/8/16/32W RMS. Peak 64W.

Nominal power 70V: 2/4/8/16/32W RMS. Peak 64W.

Power 8 Ohm: 60W RMS, 120W musical.

Suggested amplification from 10 to 100 W RMS.

Impedance 70V/100V – 8 Ohm selectable.

Frequency response 55-20000 Hz.

Sensitivity 90 dB.

Dimensions (DxH) 365x409 mm.

Weight 3 Kg.

Green colour.

UV resistant polypropylene cabinet.

IP56 protection.

Dispersion angle: 360°(O)x40°(V).

Working temperature from -20° to +60°.

* IP56 protection: Dust protection (in order not to interfere with speaker operation), water column, air flow equal to about 80 times the volume of the case. Protected against powerful water jets from any direction and sea water. Atmospheric depression 200mm.

VIVALDI

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice



Images

Vivaldi Ulisse GREEN16T



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272