



Wall speaker, 2-way, **Hi-Fi**.

Supplied with bracket for wall mounting (possible vertical slant).

Woofer 8 cm.

Tweeter 1,3 cm.

Mylar diaphragm.

Power 8 Ω : 20W RMS

Musical power 40W.

Suggested amplification from 10 to 30W RMS.

Nominal power 100V: 1,5/3/6W. 12W peak.

Selectable impedance 8 Ω - 100V

Frequency response 120-20000 Hz.

Sensitivity 85 dB.

Dispersion angle 90°Vx90°O (120° up to 3 KHz).

Max output level / full power 97 dB.

Dimensions (WxHxD) 94x140x100 mm.

Weight 0,7 Kg.

ABS cabinet, bracket and metal grille.

VIVALDI

Available colours: anthracite grey RAL9005 ([Vivaldi Ulisse MINI8B](#)) silver RAL9023 white RAL9003 ([Vivaldi Ulisse MINI8W](#)).

working temperature from -20° to +50°.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice



Images

Vivaldi Ulisse MINI8



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272

VIVALDI



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272