




In-ceiling round speaker

2 way, Hi-Fi, Frameless design

Woofer 13,5cm (5,25"), kevlar

Tweeter 1,3cm (0,5"), mylar dome, adjustable, Neodymium magnet.

Power 50W RMS.

Musical Power 100W

Suggested amplification: 10-110W RMS

Impedance: 8Ω

Frequency range: 70-20000 Hz

Sensitivity: 87 dB

Max output level full power: 99dB

Dispersion angle 120° (V/O)

Dimensions (Diam.xD): 204x77 mm

Recessed installation hole (D): 177 mm

Weight: 1,20 Kg

Installation on plasterboard, wood walls or similar: no accessories needed, the speaker is provided in the rear with hook-shaped anchors for stable fixing

Installation in-wall (concrete): [Vivaldi Ulisse SR13](#).

White colour RAL 9016, paintable (view, [Vivaldi Giove ROUND13F.R](#))

VIVALDI

Operation temperature: from -20° to +65.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice



Images

Vivaldi Giove ROUND13F



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272