



Datasheet

Vivaldi Ulisse ROUND13TL



Round speaker, 2-way built-in, Coax, Hi-Fi.

Nominal power: 10/5/2,5W. 20W peak.

Transformer voltage: 100V.

Frequency response: 55-20000 Hz.

Loudspeaker: woofer 13,5 cm fiberglass - eyeball tweeter 2,5 cm silk and aluminium.

Frequency response 55-20000 Hz.

Sensitivity 89 dB.

Dispersion angle: 120° (V/O).

Speaker dimensions (DxD) 203x75 mm.

In-built hole (D) 165 mm.

Weight 1,35 Kg.

Installation on plasterboard, wood walls or similar: no accessories needed, the speaker is provided in the rear with hook-shaped anchors for stable fixing.

Installation in-wall: not suitable.

Colour white RAL9016, paintable (please, view [Vivaldi Ulisse ROUND13TL.R](#)).

Cabinet: ABS with metal protection grille.

Working temperature from -20° to +65°.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice



VIVALDI
UNITED GROUP

Ulisse
AUDIO VIDEO PROFESSIONAL

Giove
multiroom systems



DIGITAL TECH
CONTRACTOR

multiroom e domotica audio video - diffusori HiFi - audio Home Cinema - mobili Home Cinema - audio PA e professionale



Images

Vivaldi Ulisse ROUND13TL

